



Halotron

*Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED**

**FAA Approved Model Available
(Model B394TS)**

RUGGED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction

ENVIRONMENTALLY ACCEPTABLE

- ★ EPA approved "Clean Agent" for Class A, B and C hazards
- ★ Low GWP (Global Warming Potential)
- ★ Low ODP (Ozone Depletion Potential)
- ★ Short Atmospheric Lifetime

CLEAN

- ★ Leaves no residue

USER FRIENDLY

- ★ Maximum visibility during discharge
- ★ No electrical conductivity back to the operator
- ★ No thermal or static shock
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -40°F to 120°F)

* Note: 5 lb., 11 lb. and 15 ½ lb. extinguishers are USCG approved with the bracket listed on the UL label.

Stored Pressure



**FAA Approved
(Model B394TS)**



**Models
397
398**

**Models
A384T
B385TS
B386T
B394TS**

HALOTRON I is a "Clean Agent" HydroChloroFluoroCarbon (HCFC) discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A and B fires by cooling and smothering and it will not conduct electricity back to the operator. Halotron is pressurized with Argon gas and is an EPA and FAA approved agent suitable for use on Class A, B and C fires. It has a *low* GWP of 0.04 - 0.24, *low* ODP of 0.014 (twelve times lower than the EPA maximum allowable ODP of 0.20) and a *low* Atmospheric Lifetime (3½ to 11 years).

Halotron is intended for use in areas formerly protected by Halon 1211 hand portable extinguishers such as computer rooms, telecommunications facilities, clean rooms, data storage areas, offices (for protection of sensitive electronic equipment), boats and vehicles.

**AVAILABLE IN WHEELED EXTINGUISHERS
5 YEAR WARRANTY**

SPECIFICATIONS	HALOTRON I					
	VALVES		ALUMINUM		BRASS, CHROME PLATED	
Size & Capacity (lbs.)	1.4	2½	5	5½	11	15½
Application	Nozzle				Hose & Nozzle	
Model Number	A384T	B385TS	B386T	B394TS	397	398
UL & ULC Rating	1B:C	2B:C	5B:C	5B:C	1A:10B:C	2A:10B:C
Shipping Weight (lbs.)	3¼	5¼	9½	10	22½	27½
Height (in.)	10	15½	15¼	15	21 7/8	21 7/8
Width (in.)	3¼	6 3/8	5¼	5 1/8	9¼	9¼
Depth (Diam. - in.)	2 5/8	3	4¼	4¼	6	6
Range (ft.)	6 - 8	6 - 10	9 - 15	9 - 15	9 - 15	12 - 18
Discharge Time (sec.)	9	9	9	9	9	14
Available with Chrome Plated Cylinder	Yes	Yes	Yes			
Minimum Space Requirement (cu. ft.)	196	350	700	770	1540	2170
Standard Bracket	Vehicle	Vehicle	Vehicle	Aircraft	Wall	Wall